

# WALL MOUNTED GAS MONITORS

## GUARDIAN

### FEATURES

- Direct Digital Readout With Fast Response
- Maintenance Free and Reliable
- NEMA 4X Fiberglass Enclosure
- Provides Three Alarm Levels and Fault Alarm
- Audio and Visual Alarm Indicators
- Local Danger Alarm At Sensor
- Auxiliary Output Relays For Remote Alarming
- System Test Button Checks The Electronics
- Two Year Full Warranty On System and Sensors  
(Except Oxygen Sensor With One Year Warranty)



The Guardian series are unique, reliable, wall mounted gas monitors that provide fast response to gas leaks and warn of potential danger. The early warning system alerts personnel to prevent possible larger and more dangerous levels.

The Guardian remote gas sensor/transmitter combines fuel cell technology with a diffusion limited barrier which results in a maintenance free sensor that is stable for long periods. The sensor is relatively unaffected by temperature and humidity changes. A danger alarm light and a system test switch are provided locally at the sensor/transmitter to assure proper operations.

The Guardian controller provides digital display, reset and silence alarm buttons and three visual and audible alarm levels with auxiliary relay contacts.



**CEA Instruments, Inc.**

*"EXPERTS IN TOXIC GAS DETECTION"*

# GUARDIAN SPECIFICATIONS

## TYPICAL GAS SENSORS

Carbon Monoxide (CO)	Nitrogen Dioxide (NO <sub>2</sub> )
Hydrogen Sulfide (H <sub>2</sub> S)	Nitric Oxide (NO)
Oxygen (O <sub>2</sub> )	Hydrogen (H <sub>2</sub> )
Chlorine (Cl <sub>2</sub> )	Chlorine Dioxide (ClO <sub>2</sub> )
Sulfur Dioxide (SO <sub>2</sub> )	Ammonia (NH <sub>3</sub> )
Hydrogen Cyanide (HCN)	Ozone (O <sub>3</sub> )
Hydrogen Chlorine (HCl)	

*PLEASE CONTACT US FOR ANY OTHER GAS SENSORS*

SENSOR RANGES	See the Guardian price list for available ranges
SENSOR TYPE	Three (3) electrode, electrochemical fuel cell
DIGITAL DISPLAY TYPE	Red LED, .6" high
WARRANTY	Two (2) years - sensor, transmitter, and controller (one year for Oxygen sensor)
EXPECTED SENSOR LIFE	3 to 5 years (one year for Oxygen sensor)
RESPONSE TIME	Less than 8 seconds to full alarm
SENSOR SIGNAL INPUT	4-20mA, 350 ohms maximum
REPEATABILITY	1% of full scale
DRIFT	Less than 2% per month
ALARMS	Caution, Warning, and Danger gas alarms and Problem (fault) alarm (Set to current OSHA levels unless specified otherwise)
AUDIBLE ALARM	Pulsating piezo buzzer (90dB)
RELAY CONTACTS	Problem - SPST, NO 1A @ 125VAC non-latching Danger - 2 SPDT, 10A @ 125VAC latching Relay 1 - SPDT, 10A @ 125VAC Relay 2 - SPDT, 10A @ 125VAC
POWER	110VAC - 50/60 Hz @ 200mA <i>(unless specified otherwise)</i>
DIMENSIONS	Controller - 7"h x 7"W x 5"D - NEMA 4X Remote sensor/transmitter - 3.5"H x 6"W x 3"D - NEMA 4X
WEIGHT	Controller - 4 lbs 10 oz (2.1 kilograms) Remote sensor/transmitter - 1 lb 5 oz (600 g)
TEMPERATURE RANGE	-15°C to 40 °C (5 °F to 104 °F) continuous
OPERATING HUMIDITY	15 to 90% non-condensing

*(Specifications subject to change without notice.)*



## CEA Instruments, Inc.

160 Tillman Street, Westwood, N.J. 07675 U.S.A.  
Telephone (201) 967-5660 Fax (201) 967-8450  
E-Mail: ceainstr@aol.com Website: www.ceainstr.com



# CEA Instruments, Inc.

160 Tillman Street

Westwood, N.J. 07675 USA

Phone (201) 967-5660 Fax (201) 967-8450

Website: [www.ceainstr.com](http://www.ceainstr.com) E-mail: [ceainstr@aol.com](mailto:ceainstr@aol.com)

## GUARDIAN SERIES PRICE LIST

Gas Sensor	Standard Range	Maximum*** Range
Carbon Monoxide (CO)	0-500 ppm	0-1000 ppm
Hydrogen Sulfide (H2S)	0-10 ppm	0-200 ppm
Oxygen (O2)	0-25 %	0-25 %
Chlorine (Cl2)	0-10 ppm	0-250 ppm
Sulfur Dioxide (SO2)	0-10 ppm	0-250 ppm
Hydrogen Cyanide (HCN)	0-10 ppm	0-100 ppm
Hydrogen Chloride (HCl)	0-10 ppm	0-100 ppm
Nitrogen Dioxide (NO2)	0-10 ppm	0-20 ppm
Nitric Oxide (NO)	0-50 ppm	0-100 ppm
Hydrogen (H2)	0-200 ppm	0-2000 ppm
Ammonia (NH3)	0-50 ppm	0-200 ppm
Ozone (O3)	0-10 ppm	0-20 ppm
Chlorine Dioxide (ClO2)	0-3 ppm	0-80 ppm

\*\*\*Add \$75 per channel and specify higher range if any above Standard Range is not desired

### Guardian (single channel).....\$ 1,995.00

One controller in a NEMA 4X enclosure with digital display, three audio/visual gas alarm levels (set to current OSHA levels unless specified otherwise), fault alarm LED, reset and silence alarms buttons, auxiliary relay contacts for all alarms, manual, and AC power adapter (specify 110 or 220 VAC). **One** remote sensor/transmitter in a NEMA 4X enclosure with one of the above sensors installed (specify gas and range), test button, local danger alarm LED, and twenty five (25) feet of cable.

### Guardian 2 (dual channel).....\$ 3,295.00

One controller in a NEMA 4X enclosure with an independent digital display per channel, two audio/visual gas alarm levels per channel (set to current OSHA levels unless specified otherwise), fault alarm LED and silence alarms button per channel, one reset alarms button, auxiliary relay contacts for all gas alarms per channel, manual, and AC power adapter (specify 110 or 220 VAC). **Two** remote sensor/transmitters in NEMA 4X enclosures each with one of the above sensors installed (specify gases and ranges), and each with test button, local danger alarm LED, and twenty five (25) feet of cable.

### Guardian 4 (quad channel).....\$ 5,995.00

One controller in a NEMA 4X enclosure with an independent digital display per channel, two audio/visual gas alarm levels per channel (set to current OSHA levels unless specified otherwise), fault alarm LED and silence alarms button per channel, one reset alarms button, auxiliary relay contacts for all gas alarms per channel, manual, and AC power adapter (specify 110 or 220 VAC). **Four** remote sensor/transmitters in NEMA 4X enclosures each with one of the above sensors installed (specify gases and ranges), and each with test button, local danger alarm LED, and twenty five (25) feet of cable.

#### OPTIONS

Additional sensor/transmitter cable (per foot)	\$ 2.00
4-20 mA output from controller (per channel)	\$ 250.00
External 8-hour backup battery with line noise and surge protection	\$ 900.00

#### REPLACEMENT SENSORS

Oxygen Sensor	\$ 225.00
Other Sensors (Specify target gas)	\$ 450.00

GRPL0808