

ADVANCED INFRARED MULTI-GAS ANALYZER

MGA 3000

FEATURES

- Single or multiple gas analyzers – Up to four gases at once
- Option to upgrade at later date protects initial investment
- Several different, field proven technologies utilized
- Fully supported from a single reliable source
- For use in hostile or friendly environments
- Robust, attractive, compact 3U rack mount enclosure
- Optional bench case available for non-rack mount
- Best price performance on the market
- Designed with user requirements in mind



The MGA 3000 Multi-Gas Analyser has been specifically designed to meet the needs of organizations requiring cost effective and reliable single *or* multiple gas analysis solutions. The four technologies employed are all tried and tested to ensure the user experiences maximum reliability and accuracy.

Up to four gases can be analyzed at any time. For those organizations requiring single gas analysis, but would like the option to upgrade at a later date, the MGA 3000 is an ideal solution to protect your initial investment.

Designed for use in hostile or friendly environments the MGA 3000 maintains high levels of gas selectivity wherever installed. All packed into a robust, attractive, compact 3U-rack mount enclosure to utilize minimal space. An optional bench case is available for non-rack mount installations.



CEA Instruments, Inc.

"EXPERTS IN TOXIC GAS DETECTION"

MGA 3000 SPECIFICATIONS

Technology Combinations Utilized in the MGA 3000

Criteria	Correlation Filter Technology	Single Beam Technology	Electrochemical Cell Technology	Paramagnetic Cell Technology
Gases Measured: (lowest detectable limits)	Acetylene C ₂ H ₂ to 0.5 ppm Carbon Monoxide CO to 0.1 ppm Hydrogen Chloride HCl to 5.0 ppm Methane CH ₄ to 0.5 ppm Nitric Oxide NO to 2.0 ppm Nitrous Oxide N ₂ O to 0.1 ppm	Methane CH ₄ to 0.01% Butane C ₄ H ₁₀ to 0.005% Carbon Dioxide CO ₂ to 0.001% Carbon Monoxide CO to 0.02% Nitrous Oxide N ₂ O to 10 ppm	Oxygen O ₂ to 0.1% Hydrogen Sulfide H ₂ S to 1 ppm Nitrogen Dioxide NO ₂ to 1 ppm	Oxygen O ₂ to 0.1%
Measurement Technique:	Non dispersive infrared absorption with solid state detector	Non dispersive infrared absorption with solid state detector	Electrochemical Cell	Paramagnetic Cell
Measurement Range:	Up to 100% for gases and saturation concentration for vapors	Up to 100% for gases and saturation concentration for vapors	0 to 25% O ₂ 0 to 50 ppm others	0 to 25%
Resolution:	Display: 0.1% fsd Output: ≥0.1% fsd	Display: 0.1% fsd Output: ≥0.5% fsd	Display: 0.1% Output: ≥0.025% fsd	Display: 0.01% O ₂ Output: ≥0.025% fsd
Detection Limit	0.1% fsd	1.0% fsd	-	-
Intrinsic Accuracy:	≤ 1.0% of reading	≤ 1% fsd	≤ 0.1%	≤ 0.1% O ₂
Noise:	≤0.1% fsd	≤0.5% fsd	≤0.1%	≤0.1% O ₂
Zero Stability:	≤1% fsd over a week	≤2% fsd over a week	-	-
Span Stability:	≤0.5% fsd over a week	≤0.5% fsd over a week	-	≤0.1% fsd over 6 months
Temperature Effect on Zero:	± 0.1% fsd per °C	± 0.25% fsd per °C	± 0.1% fsd per °C	± 0.1% fsd per °C
Temperature Effect on Span:	± 0.2% fsd per °C	± 0.25% fsd per °C	± 0.1% fsd per °C	± 0.1% fsd per °C
Cell Response:	Typically less than 30 secs	Typically less than 30 secs	Typically less than 30 secs	Typically less than 30 secs
Flow Rate:	Typically 0.2 to 1 liter/minute	Typically 0.2 to 1 liter/minute	Typically 0.2 to 1 liter/minute	10ml/min to 100ml/min
Flow Meter:	0.2 to 2 ml/minute			
Sample Pump:	1 liter/minute			
Electrical Connections:	Single 8 Pin DIN for all Analogue outputs. 9 way D type plug for RS232C link. XX Connector for all other Terminals.			
Gas Connections:	M6 Compression Fitting rear panel entries.			
Installation:	19" Rack Mounting. 3U High.			
Case Material:	Aluminum			
Operating Conditions:	0 to 40 °C Ambient Temperature. 0 to 95% Relative Humidity.			
Gas Conditions:	0 to 50 °C Non Condensing at Analyser entry.			
Power Requirements:	Nominal 110V / 220V / 230V User Selectable. Frequency Independent. 120VA maximum. 3 Pin IEC Connector supplied.			
Dimensions: (overall) H x W x D:	13.3 cm x 48.3 cm x 50.0 cm - 19" Rack			
Weight:	From 10 Kg to 23 Kg dependent upon configuration From 12 Kg to 25 Kg dependent upon configuration (Packed for Export)			

(Specifications subject to change without notice.)



CEA Instruments, Inc.

160 Tillman Street, Westwood, N.J. 07675 U.S.A.
 Telephone (201) 967-5660 Fax (201) 967-8450
 E-Mail: ceainstr@aol.com Website: www.ceainstr.com



CEA Instruments, Inc.

160 Tillman Street

Westwood, N.J. 07675 USA

Phone (201) 967-5660 Fax (201) 967-8450

Website: www.ceainstr.com E-mail: ceainstr@aol.com

MGA 3000 PRICE GUIDE

GAS NAME	Symbol	MINIMUM RANGES AVAILABLE		
		GC Gas Correlation Technology	EPL Extended Path Length Technology	SB Single Beam Technology
Carbon Dioxide	CO ₂	50ppm	10ppm	0.1%
Carbon Monoxide	CO	100ppm	30ppm	2.0%
Sulphur Dioxide	SO ₂	200ppm	-	1.0%
Sulphur Hexafluoride	SF ₆	-	-	0.2%
Nitric Oxide	NO	200ppm	-	-
Nitrous Oxide	N ₂ O	300ppm	100ppm	0.1%
Ammonia	NH ₃	-	-	2.0%
Methane	CH ₄	300ppm	30ppm	2.0%
Ethane	C ₂ H ₆	500ppm	-	1.0%
Propane	C ₃ H ₈	500ppm	-	1.0%
Butane	C ₄ H ₁₀	500ppm	-	0.5%
Pentane	C ₅ H ₁₂	500ppm	-	0.5%
Hexane	C ₆ H ₁₄	500ppm	-	0.5%
Heptane	C ₇ H ₁₆	500ppm	-	2.0%
Benzene	C ₆ H ₆	5000ppm	-	1.0%
Toluene	C ₆ H ₅ CH ₃	-	-	1.0%
Acetone	C ₂ H ₅ O	500ppm	-	2.0%
Hydrogen Chloride	HCL	500ppm	300ppm	-
Dichloromethane	CH ₂ CL ₂	-	-	2.0%

System requirements vary from location. Prices below should be considered as 'typical' and only be used for budgeting purposes. CEA Instruments will provide firm quotations upon user request, if provided with the complete monitoring application parameters and conditions.

ANALYSERS ONLY

MGA 3000 Gas Analyser - 1 Channel SB Technology \$ 10,995.00

MGA 3000 Gas Analyser - 2 Channel SB Technology \$ 15,995.00

MGA 3000 Gas Analyser - 3 Channel SB Technology \$ 20,995.00

or

MGA 3000 Gas Analyser - 1 Channel GC Technology \$ 15,995.00

MGA 3000 Gas Analyser - 2 Channel GC Technology \$ 23,995.00

MGA 3000 Gas Analyser - 3 Channel GC Technology \$ 31,995.00

PC BASED DATA LOGGING SOFTWARE \$ 1,995.00

Optional Software compatible with MGA 3000 systems

SPARES & CONSUMABLES PACK (Includes Consumables for Three Years)

Includes: 24 Filters, 1 kg Soda Lime (*only for CO₂ – add \$100*), Infrared Source, Shutter Motor, Sample pump, Fuses, Connectors, and Trimming Tool Long

SB System Pack \$ 1,295.00

GC System Pack \$ 1,495.00