



CEA Instruments, Inc.

160 Tillman Street

Westwood, N.J. 07675 USA

Phone (201) 967-5660 Fax (201) 967-8450

Website: www.ceainstr.com E-mail: ceainstr@aol.com

GUARDIAN SERIES PRICE LIST

Gas Sensor	Standard Range	Maximum*** Range
Carbon Monoxide (CO)	0-500 ppm	0-1000 ppm
Hydrogen Sulfide (H2S)	0-10 ppm	0-200 ppm
Oxygen (O2)	0-25 %	0-25 %
Chlorine (Cl2)	0-10 ppm	0-250 ppm
Sulfur Dioxide (SO2)	0-10 ppm	0-250 ppm
Hydrogen Cyanide (HCN)	0-10 ppm	0-100 ppm
Hydrogen Chloride (HCl)	0-10 ppm	0-100 ppm
Nitrogen Dioxide (NO2)	0-10 ppm	0-20 ppm
Nitric Oxide (NO)	0-50 ppm	0-100 ppm
Hydrogen (H2)	0-200 ppm	0-2000 ppm
Ammonia (NH3)	0-50 ppm	0-200 ppm
Ozone (O3)	0-10 ppm	0-20 ppm
Chlorine Dioxide (ClO2)	0-3 ppm	0-80 ppm

***Add \$75 per channel and specify higher range if any above Standard Range is not desired

Guardian (single channel).....\$ 1,995.00

One controller in a NEMA 4X enclosure with digital display, three audio/visual gas alarm levels (set to current OSHA levels unless specified otherwise), fault alarm LED, reset and silence alarms buttons, auxiliary relay contacts for all alarms, manual, and AC power adapter (specify 110 or 220 VAC). **One** remote sensor/transmitter in a NEMA 4X enclosure with one of the above sensors installed (specify gas and range), test button, local danger alarm LED, and twenty five (25) feet of cable.

Guardian 2 (dual channel).....\$ 3,295.00

One controller in a NEMA 4X enclosure with an independent digital display per channel, two audio/visual gas alarm levels per channel (set to current OSHA levels unless specified otherwise), fault alarm LED and silence alarms button per channel, one reset alarms button, auxiliary relay contacts for all gas alarms per channel, manual, and AC power adapter (specify 110 or 220 VAC). **Two** remote sensor/transmitters in NEMA 4X enclosures each with one of the above sensors installed (specify gases and ranges), and each with test button, local danger alarm LED, and twenty five (25) feet of cable.

Guardian 4 (quad channel).....\$ 5,995.00

One controller in a NEMA 4X enclosure with an independent digital display per channel, two audio/visual gas alarm levels per channel (set to current OSHA levels unless specified otherwise), fault alarm LED and silence alarms button per channel, one reset alarms button, auxiliary relay contacts for all gas alarms per channel, manual, and AC power adapter (specify 110 or 220 VAC). **Four** remote sensor/transmitters in NEMA 4X enclosures each with one of the above sensors installed (specify gases and ranges), and each with test button, local danger alarm LED, and twenty five (25) feet of cable.

OPTIONS

Additional sensor/transmitter cable (per foot)	\$ 2.00
4-20 mA output from controller (per channel)	\$ 250.00
External 8-hour backup battery with line noise and surge protection	\$ 900.00

REPLACEMENT SENSORS

Oxygen Sensor	\$ 225.00
Other Sensors (Specify target gas)	\$ 450.00

GRPL0808